COLUMBIA COUNTY LAND DEVELOPMENT SERVICES SEPTIC PLOT PLAN REQUIREMENTS

Note: This office does require the use of the approved Proposed and As-Built plot plan forms. Drawings showing the following information can be submitted on a separate sheet of paper (no larger than 11" x 17"), however, the approved form must accompany a separate drawing. All items may not be applicable depending on proposal.

- 1. Drawn to scale and mark scale on plan. If not to scale, then accurate dimensions must be indicated.
- 2. Property dimensions.
- 3. Direction of North.
- 4. All roads (label whether existing or proposed).
- 5. Driveways (label whether existing or proposed).
- 6. Location of structure(s) on property (label whether existing or proposed).
- 7. Location of water source: wells (whether being used or not), springs, community, or municipal.
- 8. Direction and percentage of slope.
- 9. Location of any Easements.
- 10. Proposed location of septic tank, drainfield and replacement area.
- 11. Length and spacing of drainlines.
- 12. Grade shots (elevations) at start/end points on each line, all corners of replacement field, septic tank outlet, and building sewer outlet from house.
- 13. Setback distance from septic system components to property lines and applicable structures
- 14. Location of approved test holes.
- 15. Location of all surface waters: streams, lakes, ponds, etc.
- 16. Location of any cut banks >30" (existing or proposed).
- 17. If known, any planned or existing drain locations (rain drains, curtain drains, tile drains, etc)
- 18. Construction material list must be submitted with plot plan on the approved form.

DRAINLINES AND REPLACEMENT AREA* MUST BE AT LEAST:

- 100' from any water source, regardless of whether you plan to use the water.
- 50' from intermittent streams, drain tiles, etc.
- 25-50' from cut banks or escarpments.
- 10' from property, foundation or water lines.

SEPTIC TANK & DISTRIBUTION UNIT** MUST BE AT LEAST:

- 50' from a well, creek, spring, etc. and intermittent streams, drain tiles, etc.
- 10-50' from cut banks.
- 10' from escarpments, property lines.
- 5' from foundation of any building.
- *The replacement area is the area needed for replacement whenever the original system fails.
- **The distribution unit includes any portion of the effluent sewer lines (solid pipe), pump, pressure line, dist. or drop boxes, and pre-treatment units (Sand Filter or ATT).